


InterlockingRock® PANELS

MADE IN THE USA



DESIGN NAME	AÑEJO™ PANEL ©2024 modularArts, Inc.
DIMENSIONS	32" X 32" X 1.25" (MAX RELIEF)
ORIENTATION	AS SHOWN. "THIS SIDE UP" IS DEFINED ON PANELS AS THE INTENDED ORIENTATION FOR LIGHT AND SHADOW.
WEIGHT	2.75 LBS/SQ FT
DESIGN REPEAT	32"
MATERIAL	GRG (GLASS REINFORCED GYPSUM) 100% NON-COMBUSTIBLE MINERAL
FEATURES	PRECAST MOUNT-POINTS. SELF-ALIGNING EDGES WITH STEEL REINFORCED JOINTS.
APPLICATION	NEW OR EXISTING WALLS. TYPICALLY INSTALLED DIRECTLY TO DRYWALL. MAY BE APPLIED TO A VARIETY OF SUBSTRATES (PLEASE REFER TO INSTRUCTION BOOKLET). DO NOT APPLY DIRECTLY TO STUDS.
INSTALLATION SUMMARY <ul style="list-style-type: none">· PANELS MUST BE SCREW MOUNTED THROUGH THE FACE DIRECTLY TO THE SUBSTRATE, TYPICALLY DRYWALL. PANELS ARE NOT ATTACHED TO STUDS..· ALL PANEL-TO-PANEL EDGES ARE GLUED WITH APPROVED ADHESIVE AS PANELS ARE MOUNTED. THE BACKS ARE NOT GLUED, ONLY THE PANEL EDGES.· SEAMS ARE CAULKED, EXCESS IS REMOVED AS IT IS ADDED. (DETAILED INSTRUCTIONS INCLUDED)· SURFACE MAY BE SEALED WITH A STONE SEALER OF CHOICE. (FOLLOW INSTRUCTIONS ON PRODUCT FOR NATURAL STONE, CEMENT, OR GYPSUM.) MATTE SEALERS WORK WELL WHEN HAND APPLIED. IF A PAINTED FINISH IS DESIRED, IT IS RECOMMENDED THAT THE SURFACE BE PRIMED PRIOR TO THE FINISH COAT. ONCE PRIMED, ANY FINISH OR GLOSS FACTOR MAY BE USED.	
ADDITIONAL NOTES <ul style="list-style-type: none">· 20-30 MINUTES PER PANEL SHOULD BE ALLOTTED TO MOUNT AND SEAM PANELS PRIOR TO PAINT OR SEALING. (DRYING TIME OF CAULKING NOT INCLUDED). EXPERIENCE MAY SHORTEN INSTALLATION TIME.· A DETAILED INSTALLATION BOOKLET ACCOMPANIES EACH ORDER.	