
InterlockingRock® TILES

MADE IN THE USA

CHELSEA[™] tile





DESIGN NAME CHELSEA™ TILE ©2016 MODULARARTS, INC. DIMENSIONS 16" X 16" THICKNESS 1/4" MINIMUM TO 1" MAXIMUM ORIENTATION CAN BE INSTALLED VERTICALLY OR HORIZONTALLY WEIGHT ~ 3 LBS/SQ FT **DESIGN REPEAT** 16" GRG (GLASS REINFORCED GYPSUM) 100% NON-COMBUSTIBLE MINERAL MATERIAL PRECAST MOUNT-POINTS, SELF-ALIGNING EDGES WITH STEEL REINFORCED JOINTS. FFATURES APPLICATION NEW OR EXISTING WALLS. TYPICALLY INSTALLED DIRECTLY TO DRYWALL. MAY BE APPLIED TO A VARIETY OF SUBSTRATES. DO NOT APPLY DIRECTLY TO STUDS.

INSTALLATION SUMMARY

- TILES ARE SCREW-MOUNTED THROUGH THE FACE TO THE SUBSTRATE (TYPICALLY DIRECT TO DRYWALL OR OFTEN PLYWOOD).
- · OPTIONAL (FOR EXTRA PROTECTION): SURFACE IS SEALED WITH CLEAR MATTE SEALER. SPRAY APPLICATION PROVIDES THE BEST RESULTS.
- · SEAMS ARE CAULKED WITH A MINIMAL BEAD. (50 YEAR, WHITE, PAINTABLE RECOMMENDED)
- · INSERTS ARE APPLIED BY A DURABLE ADHESIVE TAPE WHICH COMES ON THE BACK OF EACH INSERT.

ADDITIONAL NOTES

- WALNUT INSERTS ARE NOT SEALED, BUT MAY BE SEALED AFTER INSTALL ALONG WITH THE TILE IF DESIRED.
- · INSERTS ARE APPLIED AFTER INSTALLATION, WITH THE MIRROR, THIS OFFERS AN OPPORTUNITY TO SEAL THE PLASTER PART OF THE TILE (PRIOR TO ADDING THE INSERTS).
- IT IS NOTABLE THAT THE INSERTS BRIDGE THE SEAMS AND AT THE SAME TIME COVER THE MOUNT-POINTS.
- · INSERTS WILL COME WITH ADHESIVE TAPE APPLIED TO THE BACK. SHIPPED WITH THE TILES.
- THE MIRROR INSERTS HAVE A PROTECTIVE FILM TO PREVENT SCRATCHING (REMOVED BY INSTALLER).
- · 30 MINUTES SHOULD BE ALLOTTED ALLOWED TO BRING THE INSTALLATION TO A PAINT-READY STATE.
- (DRYING TIME OF CAULKING IS NOT INCLUDED.) EXPERIENCE MAY SHORTEN INSTALLATION TIME.

12/06/23



modularArts, Inc. | 206.788.4210 8207 South 192nd Street I Kent, WA 98032 modulararts.com I info@modulararts.com