


InterlockingRock® TILES

MADE IN THE USA



DESIGN NAME	CHELSEA™ TILE ©2016 MODULARARTS, INC.
DIMENSIONS	16" X 16"
THICKNESS	¼" MINIMUM TO 1" MAXIMUM
ORIENTATION	CAN BE INSTALLED VERTICALLY OR HORIZONTALLY
WEIGHT	~ 3 LBS/SQ FT
DESIGN REPEAT	16"
MATERIAL	GRG (GLASS REINFORCED GYPSUM) 100% NON-COMBUSTIBLE MINERAL
FEATURES	PRECAST MOUNT-POINTS. SELF-ALIGNING EDGES WITH STEEL REINFORCED JOINTS.
APPLICATION	NEW OR EXISTING WALLS. TYPICALLY INSTALLED DIRECTLY TO DRYWALL. MAY BE APPLIED TO A VARIETY OF SUBSTRATES. DO NOT APPLY DIRECTLY TO STUDS.
INSTALLATION SUMMARY <ul style="list-style-type: none">· TILES ARE SCREW-MOUNTED THROUGH THE FACE TO THE SUBSTRATE (TYPICALLY DIRECT TO DRYWALL OR OFTEN PLYWOOD).· OPTIONAL (FOR EXTRA PROTECTION): SURFACE IS SEALED WITH CLEAR MATTE SEALER. SPRAY APPLICATION PROVIDES THE BEST RESULTS.· SEAMS ARE CAULKED WITH A MINIMAL BEAD. (50 YEAR, WHITE, PAINTABLE RECOMMENDED).· INSERTS ARE APPLIED BY A DURABLE ADHESIVE TAPE WHICH COMES ON THE BACK OF EACH INSERT.	
ADDITIONAL NOTES <ul style="list-style-type: none">· WALNUT INSERTS ARE NOT SEALED, BUT MAY BE SEALED AFTER INSTALL ALONG WITH THE TILE IF DESIRED.· INSERTS ARE APPLIED AFTER INSTALLATION. WITH THE MIRROR, THIS OFFERS AN OPPORTUNITY TO SEAL THE PLASTER PART OF THE TILE (PRIOR TO ADDING THE INSERTS).· IT IS NOTABLE THAT THE INSERTS BRIDGE THE SEAMS AND AT THE SAME TIME COVER THE MOUNT-POINTS.· INSERTS WILL COME WITH ADHESIVE TAPE APPLIED TO THE BACK. SHIPPED WITH THE TILES.· THE MIRROR INSERTS HAVE A PROTECTIVE FILM TO PREVENT SCRATCHING (REMOVED BY INSTALLER).· 30 MINUTES SHOULD BE ALLOTTED ALLOWED TO BRING THE INSTALLATION TO A PAINT-READY STATE. (DRYING TIME OF CAULKING IS NOT INCLUDED.) EXPERIENCE MAY SHORTEN INSTALLATION TIME.	

12/06/23

modulararts®

modularArts, Inc. | 206.788.4210
8207 South 192nd Street | Kent, WA 98032
modulararts.com | info@modulararts.com

modulararts®