# InterlockingRock® PANELS

## **VENTANAS™**





DESIGN NAME	VENTANAS™ PANEL ©2019 modularArts, Inc.
DIMENSIONS	32" X 32" BY 1" MAX RELIEF
ORIENTATION	CAN BE INSTALLED VERTICALLY OR HORIZONTALLY. "THIS SIDE UP" IS DEFINED ON PANELS AS THE INTENDED ORIENTATION FOR LIGHT AND SHADOW.
WEIGHT	2.6 LBS/SQ FT
DESIGN REPEAT	32"
MATERIAL	GRG (GLASS REINFORCED GYPSUM) 100% NON-COMBUSTIBLE MINERAL
FEATURES	PRECAST MOUNT-POINTS. SELF-ALIGNING EDGES WITH STEEL REINFORCED JOINTS.
APPLICATION	NEW OR EXISTING WALLS. TYPICALLY INSTALLED DIRECTLY TO DRYWALL.  MAY BE APPLIED TO A VARIETY OF SUBSTRATES (PLEASE REFER TO INSTRUCTION BOOKLET). DO NOT APPLY DIRECTLY TO STUDS.

#### **INSTALLATION SUMMARY**

- · PANELS ARE SCREW-MOUNTED THROUGH THE FACE TO THE SUBSTRATE (TYPICALLY DIRECT TO DRYWALL).
- · SEAMS ARE CAULKED WITH A MINIMAL BEAD. (50 YEAR, WHITE, PAINTABLE RECOMMENDED)
- · OPTIONAL (FOR PAINT OR EXTRA PROTECTION): SURFACE IS SEALED WITH CLEAR MATTE SEALER. OR IF PAINTING, A PRIMER/SEAL IS REQUIRED. FLAT PAINT IS RECOMMENDED, AND SPRAY APPLICATION PROVIDES THE BEST RESULTS.

### ADDITIONAL NOTES

- 20-30 MINUTES PER PANEL SHOULD BE ALLOTTED TO MOUNT AND SEAM PANELS PRIOR TO PAINT. (DRYING TIME OF CAULKING NOT INCLUDED). EXPERIENCE MAY SHORTEN INSTALLATION TIME.
- A DETAILED INSTALLATION BOOKLET ACCOMPANIES EACH ORDER.
- VENTANAS™ IS AN EZ-SEAM™ PANEL, WHICH MEANS THAT THE VISIBLE JOINTS CAN BE CAULKED AND THE SURFACE LEFT UNFINISHED (OR SEALED) IN ITS NATURAL GYPSUM STATE. THE PRECAST MOUNT-POINTS ARE ALSO COVERED BY THE INSERTS, SO NO FILLING AND SANDING IS REQUIRED. THESE FEATURES SUBSTANTIALLY CUT DOWN ON INSTALLATION TIME AND EXPENSE.
- INSERT CHOICES: STANDARD WALNUT STANDARD WALNUT/HAND WAXED

12/06/23

## modulararts®

modularArts, Inc. I 206.788.4210 8207 South 192nd Street I Kent, WA 98032 modulararts.com | info@modulararts.com