

InterlockingRock® PANELS

MADE IN THE USA



DESIGN NAME	VENTANAS™ PANEL ©2019 modularArts, Inc.
DIMENSIONS	32" X 32" BY 1-1/2" MAX RELIEF
ORIENTATION	CAN BE INSTALLED VERTICALLY OR HORIZONTALLY. "THIS SIDE UP" IS DEFINED ON PANELS AS THE INTENDED ORIENTATION FOR LIGHT AND SHADOW.
WEIGHT	2.6 LBS/SQ FT
DESIGN REPEAT	32"
MATERIAL	GRG (GLASS REINFORCED GYPSUM) WITH LIGHTWEIGHT CLASS A FOAM CORE
FEATURES	PRECAST MOUNT-POINTS. SELF-ALIGNING EDGES WITH STEEL REINFORCED JOINTS.
APPLICATION	NEW OR EXISTING WALLS. TYPICALLY INSTALLED DIRECTLY TO DRYWALL. MAY BE APPLIED TO A VARIETY OF SUBSTRATES (PLEASE REFER TO INSTRUCTION BOOKLET). DO NOT APPLY DIRECTLY TO STUDS.
INSTALLATION SUMMARY	<ul style="list-style-type: none"> - PANELS ARE SCREW-MOUNTED THROUGH THE FACE TO THE SUBSTRATE (TYPICALLY DIRECT TO DRYWALL). - SEAMS ARE CAULKED WITH A MINIMAL BEAD. (50 YEAR, WHITE, PAINTABLE RECOMMENDED) - OPTIONAL (FOR PAINT OR EXTRA PROTECTION): SURFACE IS SEALED WITH CLEAR MATTE SEALER. OR IF PAINTING, A PRIMER/SEAL IS REQUIRED. FLAT PAINT IS RECOMMENDED, AND SPRAY APPLICATION PROVIDES THE BEST RESULTS.
ADDITIONAL NOTES	<ul style="list-style-type: none"> - 20-30 MINUTES PER PANEL SHOULD BE ALLOTTED TO MOUNT AND SEAM PANELS PRIOR TO PAINT. (DRYING TIME OF CAULKING NOT INCLUDED). EXPERIENCE MAY SHORTEN INSTALLATION TIME. - A DETAILED INSTALLATION BOOKLET ACCOMPANIES EACH ORDER. - VENTANAS™ IS AN <i>EZ-SEAM™</i> PANEL, WHICH MEANS THAT THE VISIBLE JOINTS CAN BE CAULKED AND THE SURFACE LEFT UNFINISHED (OR SEALED) IN ITS NATURAL GYPSUM STATE. THE PRECAST MOUNT-POINTS ARE ALSO COVERED BY THE INSERTS, SO NO FILLING AND SANDING IS REQUIRED. THESE FEATURES SUBSTANTIALLY CUT DOWN ON INSTALLATION TIME AND EXPENSE. - <i>INSERT CHOICES</i>: STANDARD WALNUT • STANDARD WALNUT/HAND WAXED • SOUND ABSORBENT PET IN A VARIETY OF COLORS http://www.modulararts.com/downloads/Ventanas_Inserts.zip

modulararts®

modularArts, Inc. | 206.788.4210
 2400 NW 80th St, #106 | Seattle, WA 98117
 modulararts.com | info@modulararts.com

modulararts®